BENOMIC PIPE RAIL TROLLEY



The BENOMIC series is equipped with the following as standard:

- 2x 24 V/110 AH full traction batteries •
- The driving speed is infinitely adjustable from 0-60 m per minute •
- Battery indication meter
- Simple lateral movement with one push of the button •
- The driving control is electronically adjustable for comfortable acceleration and braking •
- Simple control on the robust control panel •
- On the chassis there's a switch to control the scissors going up and down •
- Very strong and fast 0.37 kW driving motor •
- The totally welded steel structure is indestructible •
- Very stable hydraulic scissor-rack
- All powder-coated for many years of protection •
- All pipe rail sizes can be supplied •
- Always safe when going down due to hose breaking protection and emergency lowering valve •
- Integrated tilt detection as standard •
- Always provided with an original CE-declaration •
- Robust and smooth finished chassis •
- With several additional options available, please inquire about the possibilities •

Technical specifications *

Properties	Height
2 scissors	Up to 3 m
3 scissors	Up to 4.4 r
4 scissors	Up to 5.7 r

* Changes reserved



Jan v.d. Laarweg 1 2678 LH De Lier - Holland T. +31 (0)174 - 510 266 F. +31 (0)174 - 518 326 E. info@steenks-service.com I. www.steenks-service.com

height n height n height

















Č.