

# GREENLIFT GLD PIPE RAIL TROLLEY



# Specifications

- Big lifting wheels both in and out hydraulic
- Driving speed on the pipe rail adjustable from 0 to 65 m / min. and high speed button 95 m / min.
- With 24 Volt 118 Ah-5h /157Ah-20h full traction batteries
- With self-closing entry gate on both sides of the platform
- Equipped with 2 layers of powdercoating completely sandblasted beforehand
- Front and rear with special buffers
- With 450 Watt AC-drive motor with fully enclosed/chainless drive
- With cast steel driver roller and non-driver rollers for the pipe rail
- With 40 mm. wide solid rubber concrete pad wheels
- With stainless steel waterproof foot pedal
- With gas / brake function switch for the foot pedal
- With storage tray on door with control panel
- Entirely in accordance with the latest European standards, laws and regulations



## Technical specifications \*

### Properties

2 scissors GLD3500  
3 scissors GLD5000  
4 scissors GLD6500

### Height

Up to 3.5 mtr platform height  
Up to 5 mtr platform height  
Up to 6.5 mtr platform height

\* Changes reserved



Jan v.d. Laarweg 1  
2678 LH De Lier - Holland  
T. +31 (0)174 - 510 266  
F. +31 (0)174 - 518 326  
E. [info@steenks-service.com](mailto:info@steenks-service.com)  
I. [www.steenks-service.com](http://www.steenks-service.com)

