



Reisopack 2830

| | |
|---------------------|------------|
| Article code | VP0000071 |
| Selling type | New |
| Brand | Reisopack |
| Type | 2830 |
| Length | 112 cm |
| Width | 88 cm |
| Height | 293 cm |
| Direction | Horizontal |

Characteristics

Color Gray/Yellow

- ✓ strap tension: electric tension regulator for highest tension.
- ✓ voltage: 220/240 v 50/60 Hz 1 Phase
- ✓ duration 1 pallet with 4 corner boards and three bands in 55 sec.
- ✓ transport dimensions (LxWxH): 118x115x200 cm. (400 kg.) in box on pallet
- ✓ strap thickness: 0,50 - 0,85 mm.
- ✓ with handbreak
- ✓ battery charger: high frequent built into base
- ✓ heating system: electric heating system heating temperature and cooling time are adjustable
- ✓ designed and manufactured using the highest quality components
- ✓ the height of the strap can be set manually, without any difficulty
- ✓ weight: 340 kg.
- ✓ elect. Consumption: 0,5 KW
- ✓ dimensions (LxWxH): 112x88x293 cm.
- ✓ strap width: 6-8-12-15,5 mm. (standard width is 12 mm.)
- ✓ min.- max. strap height: 150-2400 mm.
- ✓ battery: 2x 6V 200Ah/5H traction battery
- ✓ with corner boards holder/dispenser
- ✓ battery indicator: digital display in base
- ✓ easy to use. The machine can be placed beside the pallet, avoiding the need to move the non-strapped pallets.

