



Reisopack 2820

| | |
|---------------------|------------|
| Article code | VP0000376 |
| Selling type | New |
| Brand | Reisopack |
| Type | 2820 |
| Length | 140 cm |
| Width | 95 cm |
| Height | 250 cm |
| Direction | Horizontal |

Characteristics

- ✓ strap tension: electric tension regulator for highest tension.
- ✓ voltage: 220/240 v 50/60 Hz 1 Phase
- ✓ duration 1 pallet with 4 pallet corners and three strapps in 55 sec.
- ✓ transport dimensions (LxWxH): 115 x 115 x 200 cm.
- ✓ strap thickness: 0,50 - 0,85 mm.
- ✓ max. strap height: 2000 mm.
- ✓ heating system: electric heating system heating temperature and cooling time are adjustable
- ✓ weight: 340 kg.
- ✓ elect. Consumption: 0,5 KW
- ✓ dimensions (LxWxH): 140 x 95 x 250 cm.
- ✓ strap width: 6-8-12-15,5 mm. (standard width is 12 mm.)
- ✓ min. strap height: 160 mm.
- ✓ with handbreak
- ✓ battery indicator: digital display at under carriage

More information about Reisopack 2820

With interchangeable set, consisting of:
+ storage trolley
+ 2x 6V 200Ah traction battery
+ high frequency battery charger
|HS-Code: 84220000

