



Strapping machine 2905 Standard

| | |
|---------------------|----------------|
| Article code | VP0001099 |
| Selling type | New |
| Brand | Reisopack |
| Type | 2905 Standaard |
| Direction | Horizontal |

Characteristics

Color Gray/Yellow

- ✓ production speed: 3 tires and cornerboards in approx. 72 sec. (excluding transport/import/export)
- ✓ pallets can be strapped long+short side leading
- ✓ mini./max. tie height: 145/2600 mm. (excluding any increases by third parties)
- ✓ machine is equipped with a double corner board magazine. You can therefore choose 2 different types or length of corner boards or you have an extra large stock (2x 40 pc.) (Based on the standard thickness of approx. 2.5 mm.)
- ✓ with each strapping, the corner boards are pressed onto the corner of the pallet
- ✓ pallets to be strapped: (loaded equal to pallet) (80x80 to 120x120 cm.)
- ✓ minimum pallet height with load for strapping with pallet corner is 1200 mm.
- ✓ electric arms that detect the pallet by means of photocells, which means that different pallet dimensions can also be strapped
- ✓ with pallet corner presses for perfect positioning of the pallet corners
- ✓ With color touchscreen, which is equipped with instructional video how to change the strap



More information about Strapping machine 2905 Standard

HS-Code: 84224000