





Reisopack 2904

| Article code | VP93 |
|--------------|-----------|
| Selling type | New |
| Brand | Reisopack |
| Туре | 2904 |

Characteristics

✓ usage: free standing as well as in a processing line

- ✓ with touchscreen
- ✓ own weight: 1.300 kg.
- ✓ electric consumption: 2kVA (2000 Watt)

✓ strapping pallets: (load equal to pallets) 1.20 x ✓ minimal strapping height: 145 mm. (exclusive 1.20 / 1.20 x 1.00 / 1.20 x 0.80 m, the pallet can be placed to the column at both positions

✓ maximal strapping height: 2700 mm. (exclusive potential expansions by third parties) ✓ PLC: Omron

Steenks Service B.V. T +31(0) 174 510 266

Jan van de Laarweg 1 F +31(0) 174 518 326

2678 LH De Lier

The Netherlands

✓ with mechanical voltage regulator

E info@steenks-service.com

W www.steenks-service.com

- ✓ voltage: 400 v 50/60 Hz 3 Phase
- ✓ production speed: 3 straps in approximately 56 sec. (exclusive transport/in-output)
- potential expansions by third parties)
- ✓ without roller track

More information about Reisopack 2904

(With free standing usage a approach angle is necessary)